

FlexAir™ Spectrum™ Saddle Mounted Disc Diffusers

Spectrum Saddle Mounted Flexible Membrane Fine Bubble Disc Diffuser Specifications



FlexAir fine bubble disc diffusers with Spectrum Saddle Mount have the following characteristics:

- Base and ring are constructed of glass filled polypropylene.
- Spectrum™ Saddle Mount withstands 700 pound edge load without failure with KlicLoc™ retainer for positive mechanical mount.
- Standard diffuser membranes are EPDM.
- Available saddle sizes: 3-inch, 4-inch, 90mm, 110mm diameter pipe
- Ceramic and membrane media options are interchangeable.

FlexAir™ Spectrum™ Saddle Mounted Disc Diffuser Pricing

Stocked	Part Number	Model	Peak Airflow		Design Airflow		Diffuser Diameter		Active Surface Area		Unit List Price
			scfm	m ³ _N /h	scfm	m ³ _N /h	in	mm	ft ²	m ²	
	02928	110mm Standard	6.0	9.5	0.5-4.0	0.9-6.8	10.9	277	0.41	0.038	\$24.00
	01797	3" Standard	6.0	9.5	0.5-4.0	0.9-6.8	10.9	277	0.41	0.038	\$24.00
	03001	3" High Capacity	10.0	15.8	1.0-8.0	1.7-13.6	10.9	277	0.41	0.038	\$24.00
	01796	4" Standard	6.0	9.5	0.5-4.0	0.9-6.8	10.9	277	0.41	0.038	\$24.00
	02114	4" High Capacity	10.0	15.8	1.0-8.0	1.7-13.6	10.9	277	0.41	0.038	\$24.00
	02019	90mm Standard	6.0	9.5	0.5-4.0	0.9-6.8	10.9	277	0.41	0.038	\$24.00

Call for quantity discount pricing.

Please contact Diffuser Express with technical questions regarding product selection.

1-877-EDI-AIR8 (334-2778) or 573-474-9456

Email: sales@DiffuserExpress.com or EDI@wastewater.com