

FlexAir™ Threaded Disc Diffusers

Threaded FlexAir Flexible Membrane Fine Bubble Disc Diffuser Specifications



FlexAir fine bubble disc diffusers have the following characteristics:

- Base and ring are constructed of glass filled polypropylene.
- Base unit connection is 3/4-inch male NPT.
- Standard diffuser membranes are EPDM.
- Available in 7-inch, 9-inch and 12-inch diameter.

FlexAir Threaded Disc Pricing

Stocked	Part Number	Model	Peak Airflow		Design Airflow		Diffuser Diameter		Active Surface Area		Unit List Price
			scfm	m ³ _N /h	scfm	m ³ _N /h	in	mm	ft ²	m ²	
	01691	7" Standard	3.0	4.7	0.5-2.5	0.9-4.3	9.0	229	0.26	0.024	\$15.00
	02001	7" High Capacity	7.5	11.9	1.0-5.0	1.7-8.5	9.0	229	0.26	0.024	\$15.00
X	01798	9" Standard	6.0	9.5	0.5-4.0	0.9-6.8	10.9	277	0.41	0.038	\$16.00
X	01799	9" High Capacity	10.0	15.8	1.0-8.0	1.7-13.6	10.9	277	0.41	0.038	\$16.00
	03493	12" Standard	10.0	15.8	1.0-8.0	1.7-13.6	13.8	351	0.73	0.068	\$28.00
	03776	12" High Capacity	18.0	28.4	2.0-13.0	3.4-22.1	13.8	351	0.73	0.068	\$28.00

Call for quantity discount pricing.

Please contact Diffuser Express with technical questions regarding product selection.

1-877-EDI-AIR8 (334-2778) or 573-474-9456

Email: sales@DiffuserExpress.com or EDI@wastewater.com